Product Data

Castrol Activ Vistra 20W-50

Smooth engine, smooth running

Description

Castrol Activ Vistra 20W-50 is a high-quality engine oil which helps to resist the effects of high temperatures found in 4-stroke motorcycle engines.

Its Super Heatguard formula works to reduce the harmful impact of high operating temperatures on critical engine components during use. Helps keep pistons clean and reduce wear to keep your motorcycle's engine running smoothly.

Application

Castrol Activ Vistra 20W-50 is suitable for motorcycles where a 20W-50 API SL (and below) and JASO MA2 (or MA) oil is recommended.

Advantages

- Gives essential protection to motorcycle's engine
- Super Heatguard formula to resist the effects of high temperatures
- Good oil consumption with oxidation control

Typical Characteristics

Name	Method	Units	Activ Vistra 20W-50
Density @ 15C, Relative	ASTM D4052	g/ml	0.8794
Viscosity, Kinematic 100C	ASTM D445	mm²/s	18.36
Viscosity, Kinematic 40C	ASTM D445	mm²/s	169.4
Viscosity Index	ASTM D2270	None	121
Pour Point	ASTM D97	°C	-30
Flash Point, PMCC	ASTM D93	°C	221

Storage

All packages should be stored under cover. Where outside storage is unavoidable drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should not be stored above 60°C, exposed to hot sun or freezing conditions.

Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

Castrol (UK) Limited, PO BOX 354, Chertsey Road, Sunbury On Thames, Middlesex, TW16 9AW

www.castrol.com