repsol lubricants

Motorcycle Oil

MXR 2T

Description

Repsol MXR 2T is a lubricant oil suitable for general usage in 2-stroke engines. Apt for a wide range of motorcycles, this product is mainly recommended for urban use. A clean oil protects the engine while keeping exhaust vents clean. Additionally, it supports very high temperature operating conditions prevalent during intensive usage due to city traffic. It also supports weight-bearing activities such as the carrying of passengers on a scooter or a small cylinder capacity motorcycle.

Properties

- Increased lubricating power reduces wear, extending the engine's life span.
- Minimizes the formation of deposits, keeping the exhaust ports clean.
- Reduces spark plug sweating and prevents the piston rings from sticking.
- Suitable for lawnmowers, chainsaws and other equipment used for DIY or small-scale agriculture.

Quality levels, approvals and recommendations

- API TC
- ISO L-EGB
- JASO M345 FB

Technical specifications

	UNIT	METHOD	VALUE
Density at 15 ºC	g/cm3	ASTM D4052	0,88
Kinematic viscosity at 100 ºC	cSt	ASTM D445	7,7
Base oil viscosity at 40 ºC	cSt	ASTM D445	53
Viscosity index	-	ASTM D2270	110
Flash point, open cup	ºC	ASTM D92	146
Pour point	ºC	ASTM D97	-15
Sulphated ashes	% in weight	ASTM D874	0,1
TBN	mg KOH/g	ASTM D2896	1,6

The above mentioned characteristics are typical values and should not be considered product specifications.